



IDC8-HD & Tiny8

P0050F0041-HD-T8



Key benefits

- > Compact control panel for Sirens, Beacon, etc.
- > Complete set of Tiny8 Console, Central Unit and FTP RJ45-Bus cable
- > Control panel is equipped with backlighting and label collection



Designers

- > CompactTiny8- 8-key console
- > Handbrake-sensitive functions
- > Overview siren and flashing light status
- > Protection:
 - Overload
 - Flooding
- > Interlock
- > Push button control
- > Permanent outputs
- > Various Auto standby modes

Homologation E13 10R05
ECE R10

Specifications

- > Operational Voltage: from +10 to +30VDC
- > 5 static positive outputs
- > 2 negative outputs
- > 4 digital inputs
(1 +Ignition, 1 positive and 2 negative)
- > Terminal type:
 - Side supply voltage
 - 14p conn AmpSeal Gold Crimp Terminal
 - RJ45 Lock
- > Weight

IDC-HD Central Unit	45g
	1.6 oz
IDC-HD Console	33g
	1,2 oz
- > Dimensions

IDC-HD Central Unit	105x113x45 mm
	4.2x4.5x1.8"
Tiny8 Console	81x39x24 mm
	3.2x1.5x1.0 inches
- > Operating temperature: from -25°C to +60°C